TIME-SET PIN
OUTSIDE—ON
INSIDE——OFF
PRESENT TIME
POWER
OUTPUT
SUL181h
SUL181h

Itemno:TB17
Operating Voltage:AC 110V/220V/240V 50~60Hz
Power Consumption:2.5V
Contace Capasity:AC220V 16A
Contact Resistance:≤50MΩ
Inaulation Resistance:≥100Ω
Operating Temperature:-40℃~+55℃
Accuracy:≤2S/天25℃
Contact Capacity:Lamp load:1000W Resistive
load:16A/250VAC(cosΦ=1)
Inductive Load:3A/250VAC(cosΦ=0.6)
Working reserve time:24hours charged can lasts 150 hours
Full Timing Range:24h
Stonage Battery:150h
Minimum Setting Unit: 30Minuters
Dimension:123X72X51mm
Weight:260g

Itemno:TB35/TB35R
Operating Voltage: AC 110V/240V
Power Consumption: 2.5V
Contace Capasity: AC220V 20A
Contact Resistance: ≤50MΩ
Inaulation Resistance: ≥100Ω
Operating Temperature: -40℃~+55℃
Accuracy: ≤2S/天25℃
Contact Capacity: Lamp load: 1000W Resistive
load: 16A/250VAC(cosΦ=1)
Inductive Load: 3A/250VAC(cosΦ=0.6)
Working reserve time: 24hours charged can lasts 150 hours
Full Timing Range: 24h
Minimum Setting Unit: 15Minuters
Setup Times: 15Minuters/time 90Time
Dimension:152X110X46mm
Weight:260g
Installing Mode: DIN rail mounting

Itemno:TB-37
Operating Voltage: AC 110V/220V/240V 50-6Hz
Power Consumption: 2.5V
Contace Capasity: AC220V 16A
Contact Resistance: ≤50MΩ
Inaulation Resistance: ≥100MΩ
Operating Temperature: -40℃~+55℃
Accuracy: ≤2S/天25℃
Contact Capacity: Lamp load: 1000W Resistive
load: 16A/250VAC(cosΦ=1)
Inductive Load: 3A/250VAC(cosΦ=0.6)
Working reserve time: 24hours charged can lasts 150 hours
Full Timing Range: 24h
Minimum Setting Unit: 15Minuters
Stonage Battery: 150h
Dimension:72X72X53mm
Weight:260g

Itemno:TB45 TB-180
Operating Voltage: AC 110V/220V/240V 50-60Hz
Power Consumption: 2.5V
Contace Capasity: AC220V 16A
Contact Resistance: ≤50MΩ
Inaulation Resistance: ≥100MΩ
Operating Temperature: -25℃~+70℃
Accuracy: ≤2S/天25℃
Contact Capacity: Lamp load: 1000W Resistive
load: 16A/250VAC(cosΦ=1))
Inductive Load: 3A/250VAC(cosΦ=0.6)
Working reserve time: 24hours charged can lasts 100 hours
Full Timing Range: 24h
Stonage Battery: 150h
Minimum Setting Unit: 15Minuters
Setup Times: 15Minuters/time 96Time
Dimension:45X17.5X60mm
Installing Mode: DIN rail mounting

Item no:TB-388
Operating Voltage: AC 100V/240V 50-60Hz
Power Consumption: 2.5V
Contace Capasity: AC220V 20A
Contact Resistance: ≤50MΩ
Inaulation Resistance: ≥100Ω
Operating Temperature: -20℃~+55℃
Accuracy: ≤2S/天25℃
Contact Capacity: Lamp load: 1000W Resistive
load: 16A/250VAC(cosΦ＝1)
Inductive Load: 3A/250VAC(cosΦ＝0.6)
Working reserve time: 24hours charged can lasts 150 hours
Full Timing Range: 24h
Minimum Setting Unit: 15Minuters
Setup Times: 15Minuters/time 96Time
Dimension:112X83.5X51mm
Weight:260g
Installing Mode: DIN rail mounting

Modle NO.		T50 AH711
Rated voltage	v	AC110-240±10%
Contact type		1NA/NC
contact capacity		
resistive load	[A]	16
inductive load	[A]	3
Rated frequency	[Z]	50-60
Time base		Quartz
Cycles		Daily
Minimum switching time	[min]	20
Max.programs per cycle		72
running reserve	[h]	200
Power dissipated	[VA]	0,5
Max.terminal section	[mm²]	1...6
Mounting		on DIN rail/wall/panel
Working temperature	[℃]	-10...+50
Ambient temperature	[℃]	-20...+60
Standards		EN60730

Item no:TB-330/TB-330R
Operating Voltage: AC 100V/240V 50-60HZ
Power Consumption: 2.5V
Contace Capasity: AC250V 30A
Contact Resistance: ≤50MΩ
Inaulation Resistance: ≥100Ω
Operating Temperature: -40℃~+55℃
Accuracy: ≤2S/天25℃
Contact Capacity: Lamp load: 1000W Resistive
load: 16A/250VAC(cosΦ=1)
Inductive Load: 3A/250VAC(cosΦ=0.6)
Working reserve time: 24hours charged can lasts 150 hours
Full Timing Range: 24h
Minimum Setting Unit: 30Minuters
Setup Times: 15Minuters/time 48Time
Dimension:188X130X55mm

Type:TS18
Rated Voltage: 100-240VAC
Frequency:50HZ/60HZ
Power Consumption:1.5W
Driving Method:Quartz controlled s stepping motor
Power compensation time:150hours
Installation： Guided rail
Load Capacity:16A 250VAC
Minimum Time-set Interval:30minutes
Ambient Temperature:-10℃~+50℃
Ambient Humidity:below85%
Size:90x54x65.5mm

Itemno:TB-72
Operating Voltage:AC 110V/220V/240V 50~60Hz
Power Consumption:2.5V
Contace Capasity:AC220V 16A
Contact Resistance:≤50MΩ
Inaulation Resistance:≥100Ω
Operating Temperature:-40℃~+55℃
Accuracy:≤2S/天25℃
Contact Capacity:Lamp load:1000W Resistive
load:16A/250VAC(cos =1)
Inductive Load:3A/250VAC(cos =0.6)
Working reserve time:24hours charged can lasts 150 hours
Full Timing Range:24h
Stonage Battery:150h
Minimum Setting Unit: 30Minuters
Dimension:123X72X51mm
Weight:260g

Itemno:TB178
Operating Voltage:AC 110V/220V/240V 50~60Hz
Power Consumption:2.5V
Contace Capasity:AC220V 16A
Contact Resistance:≤50MΩ
Inaulation Resistance:≥100Ω
Operating Temperature:-40℃~+55℃
Accuracy:≤2S/天25℃
Contact Capacity:Lamp load:1000W Resistive
load:16A/250VAC(cos =1)
Inductive Load:3A/250VAC(cos =0.6)
Working reserve time:24hours charged can lasts 150 hours
Full Timing Range:24h
Stonage Battery:150h
Minimum Setting Unit: 30Minuters
Dimension:123X72X51mm
Weight:260g

Item no:TB370
Operating Voltage: AC 100V/240V 50-60Hz
Power Consumption: 2.5V
Contace Capasity: AC220V 20A
Contact Resistance: ≤50MΩ
Inaulation Resistance: ≥100Ω
Operating Temperature: -20℃~+55℃
Accuracy: ≤2S/天25℃
Contact Capacity: Lamp load: 1000W Resistive
load: 16A/250VAC(cos =1)
Inductive Load: 3A/250VAC(cos =0.6)
Working reserve time: 24hours charged can lasts 150 hours
Full Timing Range: 24h
Minimum Setting Unit: 10Minuters
Setup Times: 10Minuters/time 120Time
Weight:260g
Installing Mode: DIN rail mounting