WiFi Din Rail Switch
Operating Manual

Smart Life APP

Download APP



- Protocol **WiFi(Default)**
- Rated operating voltage range **100V-240V**
- ControlType **Remote control, Manual**
- Poles description **1P+N (N Pole Pass-through)**
- Customization **SigMesh/ZigBee**
- Model selection **Non-metering Type Metering Type**

Non-metering Type
LED Indicator Description

The LED indicator show a steady blue light to indicate that the switch in ON status.
The LED indicator show a light out to indicate that the switch in OFF status.
The LED indicator show blue flashing to indicate that switch in paring model.

Metering Type
LED Indicator Description

The LED indicator shows a steady blue light to indicate that the network connectionis successful.
The LED indicator shows blue flashing slowly, indicating that the product inpairing model.
The LED indicator shows a light out, indicating that the device is off-grid model.
The Button indicator shows a light up to indicate that the switch is OFF
The Button indicator shows a light out to indicate that the switch is ON.



Real-time monitoring electricity consumption.

Live View

Can monitor the current, voltage, and power of the load equ-ipment in real time, and can also record the power consumption of the year, month, day, hour, and different time neriods, helping users to check the power consumption of load equipment more clearly. Setting the switch status of the equipment in different scenarios, and remotely monitor the real-time situation of the load electrical appliances.

Configuration Steps

First Step:

To connect the wire from the upper of the WiFi Din Rail Switch ,the live wire connect to the L pole, and the neutral wire connect to the N pole, please make sure that the wiring is correct and strong WiFi signal.

Second step:

Turn on the Bluetooth and WiFi of the mobile phone, open the APP and then long press the "power" button, wait for about 5-10 seconds, the LED indicator will flash blue light slowly.



Third Step:

Third Step:

Waiting for a while after graphics is displayed the APP, or click the "+" in the upper right corner, then choose the "Add Device" button to wait discovering devices, then click "Add" button.



Fourth step:

Fourth step:

Enter the wifi account password and click next step, wait for the switch to connect the network.



Fifth Step:

The switch is connected to the network.



Sixth step:

After the successful connection, the LED indicator will be changed from blue slow flashing to blue steady light.



GEYA®

ZHEJIANG GEYA ELECTRICAL CO.,LTD.

Wenzhou Bridge Industrial Zone, Beibaixiang Town, Yueqing, Zhejiang, China 325603

0086-577-62926966
0086-13567770207

sale@cngeya.com